



Intelligent Air Purification, minimalistic design & Humidification

MCK70Z

- › Onecta App Integration: control indoor with an app, via local network or internet
- › Humidification and air purification in one; covers large spaces up to 96m²
- › Intuitive display design with coloured Daikin Eye, visual way of informing users about indoor air quality
- › Pure air thanks to Daikin's 'catch and clean' approach in decomposing harmful substances
- › High performance HEPA filter with no need to change for 10 years
- › Whisper Quiet operation (down to 18dB(A))

Sensors

| | |
|--------------------------|---|
| Dust (PM2.5/dust) sensor | • |
| Odour sensor | • |
| Temperature sensor | • |
| Humidity sensor | • |

Mode

| | |
|------------------|---|
| Auto fan mode | • |
| Anti-pollen mode | • |
| Turbo mode | • |
| Quiet mode | • |
| Econo mode | • |
| Circulation mode | • |
| Moist mode | • |

Functions

| | |
|----------------------------------|---|
| Catch & clean | • |
| Deodorizing filter | • |
| Onecta app | • |
| Child proof lock | • |
| Brightness adjustment | • |
| Auto restart after power failure | • |

NEW



- Air flow up to **420 m³/h**
- Air purification up to **96 m²**
- Intelligent** air purification
- Absorbs odour via **deodorising filter**
- High Performing Electrostatic **HEPA filter**



Specifications



| Indoor Unit | | | | 70ZW/70ZBFW | | 70ZH/70ZBFH | |
|-------------------------|-------------------------|-------------------------|-------------------------|-------------------|--------------------------|-------------|--|
| Applicable room area | | | m ² | 48(1)/96(2) | | | |
| CADR | | | m ² | 375 | | | |
| Weight | Unit | | kg | 12.5 | | | |
| Dimensions | Unit | HeightxWidthxDepth | mm | 760x315x315 | | | |
| Colour | | | | White | Gray | | |
| Air flow rate | | Air purifying operation | Silent/Low/Medium/Turbo | m ³ /h | 84/132/210/420 | | |
| | | Humidifying operation | Silent/Low/Medium/Turbo | m ³ /h | 84/132/210/420 | | |
| Sound pressure level | Air purifying operation | Silent/Low/Medium/Turbo | | dBA | 18/27/37/54 | | |
| | Humidifying operation | Silent/Low/Medium/Turbo | | dBA | 18/27/37/54 | | |
| Humidifying operation | Power input | Silent/L/M/Turbo | | kW | 0.010/0.012/0.023/0.084 | | |
| | Humidification | Turbo | | ml/h | 700 | | |
| | Water tank capacity | | | l | 3.4 | | |
| Air purifying operation | Power input | Silent/L/M/Turbo | | kW | 0.010/0.011/0.020/0.082 | | |
| Power supply | Phase/Frequency/Voltage | | | Hz/V | 1~/50/60/220-240/220-230 | | |

(1)The coverage area is appropriate for operating the unit of maximum fan speed(HH). Coverage area indicates the space where a certain amount of dust particles can be removed in 30 minutes. (2)Converted to NRCC standards from test values in accordance with JEM1467. | Converted to CADR standards from test values in accordance with JEM1467. | Humidification amount changes in accordance with indoor and outdoor temperature and humidity. Measurement condition: 20°C in temperature, 30% in humidity. | Operating sound levels are the average of values measured at 1m away from the front, left, right and top of the unit. (These are equal to the values in an anechoic chamber) | Electrostatic HEPA filter and humidifying filters are attached in the unit. | Requirements according to JEM1467. | "HI" is displayed when the PM2.5 concentration exceeds 99µg/m³.